

What We Claim Is:

1. A lamp assembly for a microscope, said microscope having a stand, comprising:
a female member comprising a first electrical socket, said socket arranged to
5 provide a source of electricity for a lamp, said female receptacle located inside said
microscope stand; and,
a male member comprising:
at least two electrical pin terminals arranged to matingly engage said first
electrical socket to receive electricity therefrom; and,
10 a second socket electrically connected to said at least two electrical pin
terminals, said second socket arranged to hold said lamp and provide electricity
thereto.
2. The lamp assembly recited in Claim 1 wherein said female member comprises at
least one dowel receptacle and said male member comprises at least one alignment dowel
15 operatively arranged to align with and matingly engage said dowel receptacle.
3. The lamp assembly recited in Claim 1 wherein said microscope stand includes an
aperture formed in an external wall thereof, and said male member is keyed to said
aperture such that said male member may be inserted into said aperture in only one
orientation.
- 20 4. The lamp assembly recited in Claim 1 wherein said male member further
comprises a tab to facilitate grasping during insertion and removal of said male member
relative to said aperture.
5. The lamp assembly recited in Claim 1 wherein said lamp is a low voltage lamp
and all low voltage electricity supplied to said lamp is supplied within said stand.
- 25 6. The lamp assembly recited in Claim 1 wherein said male member is operatively
arranged to substantially flush-engage said microscope stand.
7. The lamp assembly recited in Claim 3 wherein said aperture is located in a side
wall of said stand.
8. The lamp assembly recited in Claim 3 wherein said male member comprises a
30 flange which circumscribes said male member and engages said external wall proximate
said aperture.

9. The lamp assembly recited in Claim 1 wherein said female member comprises a pair of dowel receptacles and said male member comprises a corresponding pair of alignment dowels operatively arranged to align with and matingly engage said pair of dowel receptacles.
- 5 10. The lamp assembly recited in Claim 1 wherein said lamp assembly further includes a light bulb arranged in an illumination beam path of said microscope when said male member is inserted into said female member.
11. A lamp assembly for a microscope, comprising:
a male member comprising:
10 at least two electrical pin terminals;
at least one alignment dowel; and,
a socket electrically connected to said at least two electrical pin terminals, said second socket arranged to hold said lamp and provide electricity thereto.
- 15 12. The lamp assembly recited in Claim 11 wherein said male member is keyed to an aperture formed in said microscope.
13. The lamp assembly recited in Claim 11 wherein said male member further comprises a pair of alignment dowels.
14. The lamp assembly recited in Claim 11 wherein said male member further
20 comprises a tab extending outwardly from said male member to facilitate grasping during insertion and removal of the male member.
15. A microscope stand comprising a stand having a side wall, said side wall having an aperture keyed to a lamp assembly, said microscope stand further comprising alignment and electrical connection means operatively arranged to engage said lamp
25 assembly, said electrical connection means located entirely within said stand.